



MULTI-PURPOSES RELAYS/ RELE' POLIVALENTI XR4 / XR5 /XRD5

ACCESSORIES / ACCESSORI

XR4: four lamellar connection relay.
Continuous running. (Available also at 6 Volt)
XR5: five lamellar connection relay.
Continuous running.
XRD5: five lamellar connection change over
relay. Continuous running.

XR4: Relé a 4 attacchi lamellari. Servizio continuo.
(Disponibile anche a 6 Volt)
XR5: Relé a 5 attacchi lamellari.
Servizio continuo.
XRD5: Relé in scambio, 5 attacchi lamellari.
Servizio continuo.

TECHNICAL FEATURES / CARATTERISTICHE TECNICHE

12V

24V

XR4 - item code / Codice prodotto	2400010S	2400020S
XR5 - item code / Codice prodotto	2400011S	2400021S
XRD5 - item code / Codice prodotto	2400060S	2400061S
Nominal voltage / Voltaggio nominale	12 Vdc	24 Vdc
Nominal current / Corrente nominale	30/40 A	22 A
Activation current / Corrente di attivazione	0.2 A	0.1 A
Durability / Durata	100000 cycles/cicli (1sec ON, 4sec OFF)	
Electrical insulation/Isolamento elettrico	500 Vdc	
Weight / Peso	30 gr	

Main applications:
Automotive and industrial vehicles sector
Applicazioni principali:
Settore automobilistico e veicoli industriali

Connections/Conessioni

Electrical blades connectors 6.3x0.8mm
Elettriche connettori a lama 6.3x0.8mm

MOUNTING: Install the relays on a rigid surface,
away from heat sources and water splashes.

MONTAGGIO: fissare il relé su una superficie rigida,
lontano da fonti di calore e spruzzi d'acqua.

PACKING/IMBALLO: Bulk

